

NMR imaging producing, determining position or control of system led in test object

Publication number: JP2001520057 (T)

Publication date: 2001-10-30

Inventor(s):

Applicant(s):

Classification:

- international: **A61F2/84; A61B5/055; A61B5/06; A61F2/06; A61F2/86; G01R33/28; A61F2/00; G01R33/34; A61F2/82; A61B5/055; A61B5/06; A61F2/06; G01R33/28; A61F2/00; G01R33/34; (IPC1-7): A61M29/02; A61B5/055**

- European: **A61F2/86; A61B5/055; A61B5/06; G01R33/28H**

Application number: JP20000516237T 19981013

Priority number(s): DE19971046735 19971013; WO1998DE03045 19981013

Also published as:


DE19746735 (A1)
DE19746735 (C2)
US6847837 (B1)
US6280385 (B1)
JP2001520058 (T)

[more >>](#)

Abstract not available for JP 2001520057 (T)

Abstract of corresponding document: **DE 19746735 (A1)**

The method is carried out in a locally defined region, inside or outside of the system (1), and intensifying the excitation of the nuclear spin of the object under test. The system forms or has at least one passive resonant circuit, with an inductance (2) and a capacitance (3). The resonant frequency of the circuit is essentially the same as the resonant frequency of the irradiated high frequency radiation of the nuclear magnetic resonance system. Independent claims are also included for a system for carrying out the method and an image production system.



Data supplied from the **esp@cenet** database — Worldwide